SYSTEM COMPARISON CHART	Test Criteria	NFPA 285 Compliant	ASHRAE 90.1 Compatible	Pressure Equalized	Membrane Reliant	Guttering / Controlling Joinery	Concealed Weather-Stripping	Variable Joint Size	Glazing Integrated	Low Maintenance	Non-Progressive	Face- Fastened	Joint Condition
ALUMINUM COMPOSITE MATERIAL (ACM)													
<b>DRY</b> Rout and Return Dry System	AAMA 501	•	•			•	•	•	•	•			EXTRUSIONS
PER Pressure Equalized Rainscreen	AAMA 508	•	•	•	•	•	•	•		•			EXTRUSIONS
BVR Back Ventilated Rainscreen	AAMA 509	•	•		•	•	•	•		•			EXTRUSIONS
SRS Spline Rainscreen System	AAMA 509	•	•		•		•	•		•			SPLINE
WET Rout and Return Wet	AAMA 501	•	•					•					SEALANT
SWISSPEARL (FIBER CEMENT PANELS)													
SPE Swisspearl Exposed System		•	•		•					•	•	•	OPEN
SPC Swisspearl Concealed System		•	•		•					•	•		OPEN
SPL Swisspearl Legacy System		•	•		•					•	•	•	OPEN
TRESPA (HIGH PRESSURE LAMINATE, HPL)													
110 Trespa Exposed System		•	•		•					•	•	•	OPEN
210 Trespa Concealed System		•	•		•					•	•		OPEN