

# SYSTEM COMPARISON CHART

		Test Criteria	NFPA 285 Compliant	ASHRAE 90.1 Compatible	Pressure Equalized	Membrane Reliant	Guttering / Controlling Joinery	Concealed Weather-Stripping	Variable Joint Size	Glazing Integrated	Low Maintenance	Non-Progressive	Face- Fastened	Joint Condition
<b>ALUMINUM COMPOSITE MATERIAL (ACM)</b>														
<b>DRY</b>	Rout and Return Dry System	<b>AAMA 501</b>	●	●			●	●	●	●	●			<b>EXTRUSIONS</b>
<b>PER</b>	Pressure Equalized Rainscreen	<b>AAMA 508</b>	●	●	●	●	●	●	●		●			<b>EXTRUSIONS</b>
<b>SRS</b>	Spline Rainscreen System	<b>AAMA 509</b>	●	●		●	●	●			●			<b>SPLINE</b>
<b>WET</b>	Rout and Return Wet	<b>AAMA 501</b>	●	●					●					<b>SEALANT</b>
<b>SWISSPEARL (FIBER CEMENT PANELS)</b>														
<b>SPC</b>	Swisspearl Concealed System		●	●		●					●	●		<b>OPEN</b>
<b>SPL</b>	Swisspearl Legacy System		●	●		●					●	●	●	<b>OPEN</b>
<b>TRESPA (HIGH PRESSURE LAMINATE, HPL)</b>														
<b>110</b>	Trespa Exposed System		●	●		●					●	●	●	<b>OPEN</b>
<b>210</b>	Trespa Concealed System		●	●		●					●	●		<b>OPEN</b>